

ACCUSPEC

PACKAGING CORP.

Email: accuspec@frontier.com Website: accuspecpackaging.com
607-292-3010

PRODUCT INFORMATION BULLETIN
CADPAK HD200
QPL MIL-PRF-131K

Super Heavy Duty Barrier Packaging:
Watervaporproof, Greaseproof, Flexible, Heat-
Sealable

**Structure description: Biax Nylon/PE/Cross-Lam
PE/PE/Foil/Heavy Duty Coex**

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUES	UNITS	TEST METHOD
Caliper	10.3	mil	ASTM D2103
Yield	2,650	in ² /lb	Calculated
Puncture Resistance	40	lbs	FED STD 101
Tensile Strength	48	lbs/in	ASTM D882
Tear Strength	>1,000	grams	ASTM D1922
OTR	0.0005	cc/100 in ² /day @0% RH, 23°C	ASTM D3985
WVTR	0.0005	g/100 in ² /day @ 90% RH 40°C	ASTM F1249
Seal Strength	23	lbs/in	ASTM F88
Suggested Sealing Conditions	435°F, 60psi, 3.0sec		

Disclaimer: The data presented refers to typical values only and should serve only as a guide and does not encompass normal variability, or constitute any warranty. We urge purchasers to conduct tests for suitability in their specific end use.

Accuspec Packaging Corporation
4011 County Road 25 Dundee, NY 14837
Email: accuspec@frontier.com Website: accuspecpackaging.com
607-292-3010